THIS PAGE BLANK (USPTO)

(19)

(12)

EUROPEAN PATENT APPLICATION

(21) Application number : 91402735.4

(22) Date of filing : 14.10.91

(51) Int. Cl.⁵ : **E21B 49/00, E21B 47/10**

(72) Inventor : Ehlig-Economides, Christine
32, rue Henri Régnault
F-92380 Garches (FR)

(74) Representative : Hagel, Francis et al
ETUDES ET PRODUCTIONS SCHLUMBERGER
Service Brevets B.P. 202
F-92142 Clamart Cédex (FR)

(71) Applicant : SCHLUMBERGER LIMITED
277 Park Avenue
New York, N.Y. 10172 (US)

(84) GB

(71) Applicant : SERVICES PETROLIERS
SCHLUMBERGER
42, rue Saint-Dominique
F-75007 Paris (FR)

(84) FR

(71) Applicant : SCHLUMBERGER TECHNOLOGY
B.V.
Carnegielaan 12
NL-2517 KM Den Haag (NL)

(84) DE IT

(71) Applicant : SCHLUMBERGER HOLDINGS
LIMITED
P.O. Box 71, Craigmuir Chambers
Road Town, Tortola (VG)

(84) NL

(54) **Method for individually characterizing the layers of a hydrocarbon subsurface reservoir.**

(57)   The invention relates to reservoir evaluation
and is more specifically directed to a method of
characterizing the individual response of a layer
of a multi-layer hydrocarbon reservoir traversed
by a well, based on downhole flow rate and
pressure measurements performed during tran-
sient tests initiated by changes in the surface
flow rate of the well, the flow rate being
measured above said layer during one transient
test and below said layer during another tran-
sient test. The variations of downhole pressure
and flow rate with respect to their respective
values at the initiation of the transient test are
determined, each of said flow rate variations is
normalized by the pressure variation aft r the
sam tim interval within the same transient
test, thereby to produce a first pressure-
normalized flow rate function for the level
above said layer and a second pressure-
normalized flow rate function for the level be-
low said lay r, and said first and second press-
ure-normalized flow rate functions are
subtractively combined to generate a function
representative of the individual response of said
layer.

Fig. IB Multilayer Transient (MLT) Test, with *Sequential* Pressure and Flow Rate Measure-
ments

EP 0 481 866 A2

The invention relates to a method for individually characterizing, from the standpoint of production perform-
ance, each of the producing layers of a hydrocarbon reservoir traversed by a well.

An accurate and reliable evaluation of a layered reservoir requires an evaluation on a layer-by-layer basis,
which involves that relevant parameters, such as permeability, skin factor, and average formation pressure,
can be determined for each individual layer.

A first conceivable approach for analyzing individual layers is to isolate each layer by setting packers below
and above the layer, and to perform pressure transient tests, involving the measurement of downhole pressure.
The layer is characterized by selecting an adequate model, the selection being accomplished using a log-log
plot of the pressure change vs. time and its derivative, as known in the art. But this method is less than practical
as packers would have to be set and tests conducted successively for each individual layer.

An alternative approach relies on downhole measurements of pressure and flow rate by means of produc-
tion logging tools. A proposal for implementing this approach has been to simultaneously measure the flow rate
above and below the layer of interest, whereby the contribution of the layer to the flow would be computed by
simply subtracting the flow rate measured below the layer from the flow rate measured above this layer. This
in effect would provide a substitute for the isolation of a zone by packers. But this proposal has suffered from
logistical and calibration difficulties that have thwarted its commercial application.

A more practical testing technique, called Multilayer Transient (MLT) testing technique, is described by
Shah et al, "Estimation of the Permeabilities and Skin Factors in Layered Reservoirs with Downhole Rate and
Pressure Data" in SPE Formation Evaluation (Sept. 1988) pp. 555-566. In this technique, downhole measure-
ments of flow rate are acquired with only one flowmeter displaced from one level to another level. Flow rate
measurements are thus acquired at different times. However, because fluctuations may occur in the surface
flow rate, and also because the change imposed on the surface flow rate to initiate a transient is of arbitrary
magnitude, it is not possible to determine the contribution of an individual layer by simply subtracting from each
other the flow rates measured below and above the layer. This complicates the interpretation of test data.

The object of the invention is to enable each layer of a multi-layer reservoir to be characterized on an indi-
vidual basis from downhole flowrate and pressure transient measurements.

A further object is to enable such characterization without impractical requirements insofar as acquisition
of measurement data is concerned being imposed.

The invention will be made clear from the following description, made with reference to the attached draw-
ings.

In the drawings :

– figure 1A illustrates the isolated zone testing technique, in the case of a three-layer reservoir;

– figure 1B illustrates the multilayer transient (MLT) testing technique;

– figure 2 shows an example of a test sequence suitable for evaluating the individual responses of the layers
with the MLT technique;

– figure 3 is a flow chart describing the method of the invention, with rectangular blocks showing compu-
tation steps and slanted blocks showing input data for the respective computation steps;

– figure 4 compares the results of the method of the invention with those obtained from the isolated testing
technique, based on a simulated example.

In the case of a single-layer hydrocarbon reservoir, well testing techniques allow the properties (permeabi-
lity, skin factor, average formation pressure, vertical fracture, dual porosity, outer boundaries,...) of the reser-
voir - more exactly, of the well-reservoir system - to be determined. A step change is imposed at the surface
on the flow rate of the well, and pressure is continuously measured in the well. Log-log plots of the pressure
variations vs. time and of its derivative are used to select a model for the reservoir, and the parameters of the
model are varied to produce a match between modelled and measured data in order to determine the properties
of the reservoir.

In the case of a layered reservoir such as the three-layer reservoir shown in figures 1A and 1B, a complete
characterization of the reservoir implies the determination of such parameters as permeability, skin factor, aver-
age pressure (and others where applicable) for each of the individual layers, because the same model cannot
be assumed for all layers. Therefore, such parameters can only be derived from well test data if an adequate
model can be ascertained for each layer.

Figure 1A illustrates the conventional testing technique in which fluid communication between the well and
the reservoir is restricted to a particular zone isolated by means of packers set above and below this zone, and
a test is performed by first flowing the well and then shuting it in, and m asuring the variations vs. time of the
pressure in the well during the time the well is shut in. Such a technique allows the response of each individual
layer to be analyzed, one at a time, since the pressure measured in the isolated portion of the well will only
depend on the properties of the flowing layer.

Figure 4 shows simulated pressure and pressure derivative plots vs. elapsed Δt - the elapsed time for each

2

isolated zone test starting from the onset of flow. For computing the simulation, the following properties have been used for the respective layers :

Reservoir and Fluid Properties for Simulated Example

Layer	h(ft)	Φ	k(md)	Skin	x_f(ft)	λ	ω	r_e(ft)
1	10	0.20	300	3	–	–	–	200
2	15	0.15	100	0	–	1.10^{-4}	0.05	200
3	50	0.10	15	–	50	5.10^{-5}	0.01	∞

$$r_\omega = 0.4 \text{ ft} \qquad\qquad B = 1.0 \text{ RB/STB}$$
$$c_t = 1.10^{-5}/\text{psi} \qquad\qquad \mu = 1.0 \text{ cp}$$

with the following definitions :

h   thickness of the layer
Φ porosity
k   permeability
x_f vertical fracture half-length
λ interporosity flow parameter
ω storativity ratio
r_e external boundary radius

Figure 4 shows respective pressure and pressure derivative plots for zones 1, 2 and 3. For instance, layer 1 is characterized by the pressure and pressure derivative curves in full line. By identifying such features in these curves as the slope of the late-time portion, etc, a model can be diagnosed for layer 1. For more information on model selection, reference is made to Ehlig-Economides, C. :"Use of Pressure Derivative in Well Test Interpretation" SPE-Formation Evaluation (June 1989) 1280-2.

Figure 1B illustrates an alternative testing technique, called MLT (Multilayer Transient), which makes use of downhole measurement of flowrate in addition to pressure. A production logging string, including a pressure sensor 10 and a flowmeter 11, is lowered into the well. The logging string is suspended from an electrical cabl 12 which conveys measurement data to a surface equipment, not shown.

For each test, starting with a change in the surface flow rate, the logging string is positioned above the layer of interest so that the flow rate measured by the flowmeter includes the contribution from that layer. The logging string is kept at this level throughout the test, and is thus caused to operate in a stationary mode. Pressure and flow rate are acquired at a high sampling rate, e.g. every second, during each test. Figure 2 shows simulated data illustrating a possible test sequence and the acquired downhole data (with "BHP" standing for downhole pressure and "BHF" for downhole flow rate).

A method will now be described whereby a substitute for the single layer responses as obtained by isolated zone tests can be derived from MLT test data.

We assume that transient tests have been performed with the flowmeter respectively above the upper limit and below the lower limit of a zone I of the well corresponding to the layer of interest. Evidently, measurements acquired with the flowmeter below the lower limit of zone I will also be used as the flow rate measurements above the upper limit of the zone lying immediately below zone I.

Let T_k, T_l be the start times of the two transient tests, performed with the flowmeter respectively above and below the layer of interest, and Δt the elapsed time within each test. Pressure measurements yield the variation of pressure vs. elapsed time :

$\Delta p_{wf}(T_k + \Delta t)$ for the test starting at T_k
$\Delta p_{wf}(T_l + \Delta_t)$ for the test starting at time T_l.

Flowrate measurements acquired at level J above zone I during the test starting at tim T_k yield a flow rate variation :

$[\Delta q(T_k + \Delta_t)]_J$

Likewise, flow rate measurements acquired at level J+1 below zone I during the test starting at time T_l yield the flow rate variation :

$[\Delta q(T_l + \Delta t)]_{J+1}$

We normalize the MLT data obtained during the test starting at T_k by forming, for each value of elapsed time Δt_i, the ratio of the flow rate variation to the simultaneous pressure variation :

3

$$PNR_J(\Delta t_i) = \frac{[\Delta q(T_k + \Delta t_i)]_J}{\Delta p_{wf}(T_k + \Delta t_i)}$$

The same computation yields for the test starting at T_l a ratio:

$$PNR_{J+1}(\delta t_i) = \frac{[\Delta q(T_k + \Delta t_i)]_{J+1}}{\Delta p_{wf}(T_l + \Delta t_i)}$$

The pressure-normalized ratios pertaining respectively to level J above zone I and level J+1 below zone I are subtractively combined to provide a time-dependent data set which characterizes the individual response of layer I.

In the described embodiment, a suitable entity is formed as the reciprocal of the difference between the ratios PNR_J and PNR_{J+1} :

$$RPNR_I = \frac{1}{PNR_J(\Delta t_i) - PNR_{J+1}(\Delta t_i)}$$

Although the measurements above and below zone I are made at different times and follow changes in surface flow rate which may be (and are generally) different in magnitude, the ratios PNR_J and PNR_{J+1} may be subtracted because the normalization provides correction for flow rate fluctuations and for the magnitude of the flow rate change which has initiated the transient.

The "reciprocal pressure-normalized rate" (RPNR) pertaining to layer I is a suitable substitute for the pressure change obtained in the context of an isolated zone test. A log-log plot of the RPNR vs. elapsed time thus provides a response pattern for the layer of interest.

Likewise, the log-log derivative plot of the RPNR vs. elapsed time provides an equivalent to the pressure derivative response obtained in an isolated zone test.

Superposition effects may have to be taken into account. Superposition effects result from the fact that the well has produced at different rates. When the rate is increased from a first value Q1 to a second value Q2, the measured pressure drop will be the sum of the pressure change resulting from the change in the rate and the pressure changes resulting from previous rate changes, including Q1 (see Matthews and Russell, Pressure Buildup and Flow Tests in Wells pp. 14-17, Vol. 1 - Henry L. Doherty series, SPE-AIME, 1967). Superposition effects may be insignificant if the change in the surface rate is a large increase. However, superposition effects may entail gross distortions in the case of a decrease in flowrate, particularly for features pertaining to reservoir boundaries.

Correction for superposition involves that derivation of the RPNR be made with respect to a superposition time function rather than to elapsed time Δt. In this respect, reference is made to a publication SPE 20550 "Pressure Desuperposition Technique for Improved Late-Time Transient Diagnosis" by C.A. Ehlig-Economides et al. The following description relies upon this work and will refer to the equations presented in this referenc as "SPE 20550 Equ." followed by its number.

The RPNR derivative is computed so as to correct for superposition effects, in the manner described below in detail with reference to the flow chart of figure 3.

The result of the computation is the RPNR derivative for every layer. Fig. 4 shows such RPNR derivatives for zones 1, 2 and 3 and compares them with the respective single-layer pressure derivative plots which would result from the isolated zone test. It is apparent from figure 4 that the RPNR derivative mimics the single-lay r pressure derivative as regards the meaningful features of the curves (trough, inflection points, line slopes).

The RPNR and RPNR derivative are thus efficient tools for individually characterizing a given layer i.e. for diagnosing a model for this layer.

It is to be noted that for the RPNR and RPNR derivative to be determined, no specific constraint is impos d on the test sequence. The only requirement is that in addition to pressure, measurements of downhole flow rate variations vs. time are available both above and below the layer under investigation.

The flow chart of figure 3 provides a detailed description of the steps involved in the computation of the RPNR derivative. Rectangular blocks indicate computation steps while slanted blocks indicate data inputting steps.

Input block 20 recalls the above-mentioned definitions of flow rate q_j, q_{j+1} and pressure p_{wf} measured downhole during MLT tests. J is the level above the zone of interest, J+1 is the level below that zone. The elaps d time variable Δt_i is defined within each transient test, the starting point being the time T_k, T_l, of change in the surfac flow rate.

Th computations of block 21 provide the pressure change variation and downhole flowrate chang variation vs. laps d time.

The respective pressure-normaliz d rates PNR for levels J and J+1 are computed as explained above and recall d in block 22.

Block 23 recalls the computation of th RPNR pertaining to the zone lying between levels J and J+1, defined

as the reciprocal of the difference of the PNR's.

Input block 24 indicates that the input data for superposition correction (also called desuperposition) are the production rate history data : the times of surface rate changes $T_1 .. T_l$, the surface flow rates $Q(T1)$, $Q(T2)$ ..., with $Q(T1)$ being the rate from time 0 to T_1, and the downhole flow rates $q(T1)$, etc.

Block 25 gives the expression for the superposition time function t_{sup}, corresponding to SPE 20550 Equations (16), (8) brought together. This function is computed for the transient which is considered representative i.e. which shows minimal distortion in its late-time period. As explained above, due to superposition, distortion will be minimal for the test which starts with the largest increase in surface rate. Block 26 indicates that the derivative of pressure variation with respect to the superposition time function t_{sup} is computed for the representative transient mentioned above.

The computation of block 26 yields, for this representative transient, the derivative of pressure change with respect to the superposition time function t_{sup}. From a log-log plot of this pressure derivative vs. elapsed time, the slope $\underline{a}$ of the late-time portion is computed, as indicated by block 27.

Then, based on the assumption that the pressure change follows a trend represented by

$$\Delta p_{wf}(\Delta t) = m_e(\Delta t)^a + b$$

the slope m_e is computed as indicated by block 28 and explained in that portion of SPE20550 which follows Equation (21).

A desuperposition pressure function $psup_e(\Delta t_i)$ is then computed as indicated in block 29, after SPE20550 Equation (20).

This leads to a corrected pressure change :

$$\Delta p_{wf}(\Delta t_i) - psup_e(\Delta t_i)$$

Block 30 indicates that the function known in the art as a deconvolution Δp_{dd}, can then be derived from this data set. At this point, a choice between two routes must be made depending on the "smoothness" of the deconvolution data set Δp_{dd} obtained from the step of block 30. The data will be considered "smooth" if they provide a definable pattern. If on the contrary, the data are erratic and show no consistent pattern, they are "not smooth". Thus block 31 consists of a test as to the "smoothness" of the data set $\Delta p_{dd}(\Delta t_i)$.

The general expression for the RPNR derivative with respect to $\ln(\Delta t)$ is as follows :

$$\frac{DRPNR_{IJ}(\Delta t_i)}{d\ln(\Delta t)} = (RPNR_{IJ}(\Delta ti))^2 \left[\frac{dRNP_J(\Delta t_i)}{d\ln(\Delta t)} (PNR_J(\Delta t_i))^2 \right.$$

$$\left. - \frac{dRNP_{J+1}(\Delta t_i)}{d\ln(\Delta t)} (PNR_{J+1}(\Delta t_i))^2 \right]$$

If the answer to the test 31 is "Yes", then the RPNR derivative can be computed by substituting the deconvolution derivative

$$\frac{d\Delta pdd}{d\ln(\Delta t)}$$

for the derivative $\ln(\Delta t)$ of the rate normalized pressure $RNP(\Delta t_i)$, which is the reciprocal to the pressure-normalized rate PNR.

This leads to the expression of block 32 for the RPNR derivative.

If the data are not sufficiently smooth, recourse will be had to the downhole rate-convolved time function t_{SFRC}, expressed by SPE20550 Equ.(24), recalled in block 33. An approximate RPNR derivative can then be computed by the expression indicated in block 34, obtained by substituting the corrected convolution derivative :

$$\frac{p_{sup}(\Delta t_i) - RNP(\Delta t_i)}{dt_{SFRC}}$$

for the derivative vs. $\ln(\Delta t)$ of $RNP(\Delta t_i)$.

Claims

1. A method of characterizing the individual response of a layer of a multi-layer hydrocarbon reservoir traversed by a well, from downhole flow rate and pressure measurements performed during transient tests initiated by changes in the surface flow rate of the well, comprising the steps of :
   - determining, for each time interval after the initiation of the respective transient, the variations of downhole pressure and flow rate with respect to their respective values at the initiation of the transient test, the flow rate being measured above said layer during one transient test and below said layer during another transient test,
   - normalizing each of said flow rate variations by the pressure variation after the same time interval within the same transient test thereby to produce a first pressure-normalized flow rate function for the level above said layer and a second pressure-normalized flow rate function for the level below said layer, and
   - subtractively combining said first and second pressure-normalized flow rate functions to generate a function representative of the individual response of said layer.

2. The method of claim 1, wherein the combining step comprises forming the reciprocal of the difference between said first and second pressure-normalized flow rate functions.

3. The method of claim 1 or claim 2, comprising the step of differentiating with respect to logarithm of time said representative function to form a derivative function representative of the individual response of the layer.

4. The method of claim 3, wherein the differentiating step includes correction for the effects of superposition resulting from changes in the surface flow rate of the well prior to each transient test.

6

Fig. 1A Isolated Zone Test

Fig. IB Multilayer Transient (MLT) Test, with *Sequential* Pressure and Flow Rate Measurements

Fig. 2 Test Sequence for Simulated Example

$$\boxed{\text{PNR and RPNR Computation Flow Chart}}$$

20

Input $\Delta t_i = 0, t_1 - t_0, t_2 - t_0, \cdots, t_i - t_0, \cdots; t_0 = T_{k,l};$

$q_J(T_k + \Delta t_i), P_{wf}(T_k + \Delta t_i), q_{J+1}(T_l + \Delta t_i), P_{wf}(T_l + \Delta t_i)$ for $i = 1, \cdots, k, \cdots, l$

21

Compute $[\Delta q(T_{k,l} + \Delta t_i)]_{J,J+1} = q_{J,J+1}(T_{k,l} + \Delta t_i) - q_{J,J+1}(T_{k,l})$

$\Delta p_{wf}(T_{k,l} + \Delta t_i) = p_{wf}(T_{k,l} + \Delta t_i) - p_{wf}(T_{k,l})$

22

Compute $PNR_{J,J+1}(\Delta t_i) = \dfrac{[\Delta q(T_{k,l} + \Delta t_i)]_{J,J+1}}{\Delta p_{wf}(T_{k,l} + \Delta t_i)}$

23

Compute RPNR difference :

$$RPNR_{IJ}(\Delta t_i) = \frac{1}{PNR_J(\Delta t_i) - PNR_{J+1}(\Delta t_i)}$$

24

Input times for surface rate changes :

$$T_1, T_2, \cdots, T_k, \cdots, T_l;$$

and downhole and surface rates :

$$q_{J,J+1}(T_1), q_{J,J+1}(T_2), \cdots, q_{J,J+1}(T_{k,l}); Q(T_1), Q(T_2), \cdots$$

25

Compute t_{sup} for representative transient :

$$t_{sup} = \frac{1}{(Q_{n+1} - Q_n)} \sum_{j=0}^{n-1} (Q_{j+1} - Q_j) \ln\left(\frac{T_n - T_j}{T_n - T_j + \Delta t}\right) - \ln(\Delta t)$$

26

Compute $\dfrac{d\Delta p_{wf}(\Delta t)}{dt_{sup}}$ for representative transient.

$\boxed{A}$

FIG_3

27 — Compute slope, a, of late-time pressure derivative on plot of $\log\left[\dfrac{d\Delta p_{wf}(\Delta t)}{dt_{sup}}\right]$ versus $\log(\Delta t)$.

28 — Compute slope, m, for same late-time data on plot of $p_{wf}(\Delta t)$ versus $(\Delta t)^a$ for $a \neq 0$, or $p_{wf}(\Delta t)$ versus $\ln(\Delta t)$ for $a = 0$.

29 — Compute $p_{sup_e}(\Delta t_i)$ using Eq. (20)[1] for $a \neq 0$, or

$$p_{sup_e}(\Delta t_i) = \frac{m_e}{Q_{n+1} - Q_n} \sum_{j=0}^{n-1} (Q_{j+1} - Q_j) \ln\left(\frac{T_n - T_j}{T_n - T_j + \Delta t_i}\right), \text{ for } a = 0.$$

30 — Compute the deconvolution, $\Delta p_{ddJ,J+1}(\Delta t_i)$, from the following systems of equations:

$$\Delta p_{wf}(\Delta t_i) - p_{sup_e}(\Delta t_i) = \sum_{l=0}^{k,l-1} (Q_{i+1} - Q_i)_{J,J+1} \Delta p_{ddJ,J+1}(T_{k,l} - t_i).$$

31 — ◇ DATA SMOOTH ? — Y / N

32 — If the $\Delta p_{ddJ,J+1}(\Delta t_i)$ are sufficiently smooth, compute the RPNR derivative as follows:

$$\frac{d\Delta p_{ddIJ}(\Delta t_i)}{d\ln(\Delta t)} = (RPNR_{IJ}(\Delta t_i))^2 \left[\frac{d\Delta p_{ddJ}(\Delta t_i)}{d\ln(\Delta t)}(PNR_J(\Delta t_i))^2\right.$$
$$\left. - \frac{d\Delta p_{ddJ+1}(\Delta t_i)}{d\ln(\Delta t)}(PNR_{J+1}(\Delta t_i))^2\right]$$

33 — If the $\Delta p_{ddJ,J+1}(\Delta t_i)$ are not sufficiently smooth, compute t_{SFRC_0}:

$$t_{SFRC_0} = \frac{1}{(q_0 - q_k)} \left[\sum_{i=1}^{k-1} (q_0 - q_i)\ln\left(\frac{T_k - t_{i-1}}{T_k - t_{k-1}}\right) + (q_0 - q_k)\ln(t_k - t_{k-1})\right].$$

34 — Compute approximate RPNR derivative :

$$\frac{dRPNR_{IJ}(\Delta t_i)}{d\ln(\Delta t)} = (RPNR_{IJ}(\Delta t_i))^2 \left[\frac{d|p_{sup_e}(\Delta t_i) - RNP_J(\Delta t_i)|}{dt_{SFRC_0}}(PNR_J(\Delta t_i))^2\right.$$
$$\left. - \frac{d|p_{sup_e}(\Delta t_i) - RNP_{J+1}(\Delta t_i)|}{dt_{SFRC_0}}(PNR_{J+1}(\Delta t_i))^2\right]$$

where $RNP_{J,J+1}(\Delta t_i) = \dfrac{1}{PNR_{J,J+1}(\Delta t_i)}$.

FIG. 3 (cont'd)

Fig. 4 Comparison of Isolated Zone Test Response with RPNR and RPNR Derivative for Three Zones Tested